

Microwave antenna

AL3-17/MP

ALCOMA

Microwave antenna description


High Performance 0.90 m antenna for point to point links.

General parameters

Diameter	0.9 m (3 ft.)
Feeder	dual polarized
Input flange standard	circular, hole diameter 10.99 mm
Polarization	dual
Environmental temperature	-45 °C ÷ +55 °C
Color	gray
Radom material	plastic tilt
Radom color	white

Electrical parameters


Frequency band	17.100 - 17.300 GHz
Gain mid band	42.0 dBi
3dB - BW	1.4° (H/ V)
Return loss	> 1.20 (20 dB)
F/B ratio	61 dB
XPD	32 dB
Class	2 or 3 (ETSI EN 302 217)



Microwave antenna AL3-17/MP

Mechanical parameters

Performance stability	up to 30 m/s (110 km/h)
Survival	up to 55 m/s (200 km/h)
Net weight	26 kg
Pipe diameter	73 - 115 mm
Fine adjust Azimuth	$\pm 7^\circ$
Fine adjust Elevation	$\pm 15^\circ$



Forces and twisting moment due wind and ice

Wind velocity	30 m/s (110 km/h)	55 m/s (200 km/h)
F_a - axial force	560 N	1850 N
F_s - side force	180 N	570 N
M_t - twisting moment	200 Nm	640 Nm
Vertical load due to radial ice 25 mm (ice density 7kN/m ³)	430 N	

Outlines

